



TB60 Top Bender®

Tube & Pipe Bending Machine

 **Fabricators Favorite**

*Additional Savings when Purchasing
Tooling Kit with Machine*

TB60 with Pipe Kit • Part# TB60P

Pipe Size	CLR	Min. Wall	Center Former Part #	Counterbend Die Part #
½"	1.8	.109	153R046P0500	155P0500
¾"	2.2	.113	153R056P0750	155P0750
1"	2.6	.133	153R067P1000	155P1000
1¼"	3.5	.140	153R090P1250	155P1250
1½"	3.9	.145	153R100P1500	155P1500
2"	5.9	.109	153R150P2000	155P2000

Pipe Kit only Part# PIPEKIT1

TB60 with "Small Radius" Tube Kit Part# TB60TSR

Tube Size	CLR	Min. Wall	Center Former Part #	Counterbend Die Part #
¾"	2.6	.035	153R067T0750	154T0750
⅞"	2.2	.065	153R056T0875	154T0875
1"	2.6	.065	153R067T1000	154T1000
1¼"	3.2	.083	153R082T1250	154T1250
1½"	3.9	.083	153R100T1500	154T1500
2"	5.9	.095	153R150T2000	154T2000

"Small Radius" Tube Kit only Part# TUBEKIT1SR

TB60 with "Large Radius" Tube Kit Part# TB60T

Tube Size	CLR	Min. Wall	Center Former Part#	Counterbend Die Part#
¾"	2.6	.035	153R067T0750	154T0750
⅞"	2.6	.035	153R067T0875	154T0875
1"	3.2	.035	153R082T1000	154T1000
1¼"	4.4	.035	153R112T1250	154T1250
1½"	5.9	.049	153R150T1500	154T1500
1¾"	6.7	.065	153R170T1750	154T1750
2"	7.5	.065	153R190T2000	154T2000

"Large Radius" Tube Kit only Part# TUBEKIT1



Part# TB60
machine only



Ercolina's Most Popular Workhorse

FEATURES

- Ideal for producing consistent quality bends in pipe, tube, squares, solids and other profiles
- Touch screen programming of bend angle with system diagnostics in multiple languages
- Quick-change tooling system with multiple radii available
- Digital display of bend angle
- Bend any angle to 180° with independent material springback compensation for each bend
- Two bend speeds
- Foot pedal control for hands-free operation
- Swing away counterbending die vise for easy material handling
- Counterbending die position monitored electronically for accuracy and repeatability
- Accepts Ercolina's A40-P two axis positioning table for multiple and sequential bends
- Compact design with base wheels and lift handle
- No hydraulic components
- Individual tooling available on pages 15-25

TB60 Capacities & Specifications

Tube (Min.)	1/4"
(Max.)	2 1/2"
Pipe (Max.)	2" Sch. 40
Centerline Radius (Min.)	2 x Ø
(Max.)	15"
Degree of Bend	0-210°
Bending Speed	Variable
Programming	NC with Touchpad (30) programs (9) bends per program
Material Positioning Table	Available (see page 30)
Voltage	220V or 480V 3ph
Length, Width, Height	27" x 15" x 36"
Weight	430 lbs.

All capacities based on A53 grade A 48,000 psi tensile materials; heavy wall and high tensile materials reduce machine capacity.
Consult supplier for material specifications.

POPULAR ACCESSORIES



Tube & Pipe Tooling Kits




Spray Lubricant



Two Axis Positioner



Easy Part Layout Software



Square Tooling

Tooling Kits [Pages 15-16](#)

Tooling and
Accessories [Pages 17-25](#)

Model Comparison
Guide [Page 32](#)



◀ Ercolina Bending Application

**Product
Demonstrations
Available on Website**

**NEED ADDITIONAL HELP?
CONTACT ERCOLINA:**

563.391.7700

info@ercolina-usa.com

ercolina-usa.com